

WINDOWS**AUSSEN ÖFFNENDE
FENSTER RIVA AWS 50**

Excellent thermal insulation and versatile implementation possibilities. The outward opening windows from BENEDICT + RIVA are impressive with excellent thermal insulation, versatile implementation possibilities, and easy processing. The comfort level in the building is significantly increased with outward opening windows from RIVA, not least through the space that is gained. With a maximum size for top-hung windows of 2000 mm x 2000 mm and optional concealed fittings, there is a high degree of design freedom for the rigorous requirements of apartment and home construction.

**Product information:**

- Suitable for use in private apartment and home construction, as well as in commercial real estate
- Center gasket in co-extrusion
- Different opening types, optionally with concealed fittings

DESIGN SPECIFICATIONS

Face width	91 mm
Face width window frame min. - max.	51 mm
Face width casement frame min. max.	40 mm
Face width mullion min. - max.	76 - 250 mm

SUSTAINABILITY

Corrosion protection class	class 5
Uf-value frame ?	2,5 W/(m ² ·K)
Wind load resistance	class C5/B5
Certificates	cradle2cradle SILVER

TECHNICAL SPECIFICATIONS

Fall prevention yes

Barrier-free operating force as specified in DIN 1840 yes

Operating forces class 1

CE mark yes

FUNCTIONS

Barrier-free ? 20 mm

Break-in resistance up to RC 1

Opening type to the outside side-hung, double-vent side-hung / side-hung, projected top-hung, projected side-hung, horizontal pivot, vertical pivot

Opening type to the inside turn/ tilt, side-hung, bottom-hung, double-vent turn / tilt / side-hung, double-vent side-hung / side-hung, tilt / slide, toplight, horizontal pivot, vertical pivot, tilt-before-turn



We are experts in designing, manufacturing and installing complex facades.

