

DOORS

RIVA ADS 75.SI

Exterior doors that guarantee high lock and key security – DIN tested. The RIVA ADS 75.SI (Super Insulated) exterior doors are doors that differ from conventional house doors through their robust design and tested fittings systems in accordance with DIN 18251. This exterior door is suitable for high-traffic areas and wherever lock and key security should be ensured. It can be integrated in the planned building automation and meets the highest energy-efficiency requirements. The exterior door from BENEDICT + RIVA offers a maximum standard of sound reduction and in addition a combination EPDM and aluminum barrier-free threshold. For an architectural design that does not neglect a pleasant room climate.


Product information:

- For buildings with the most rigorous energy management requirements
- Ideal as a multi-function door for building automation
- Harmonizes effectively with facades and window systems

DESIGN SPECIFICATIONS

Face width	min. 147 mm
Vent variant	all-around, sill-rail profile
Filling type	insert panel infill, door infill, leaf enclosing on one side, door infill, leaf-enclosing on two sides
Overall system depth min. - max.	75 mm

TECHNICAL SPECIFICATIONS

National technical approval	yes
CE mark	yes
Verification of permanent functionality	class 6
Vent weight max.	150 kg

SUSTAINABILITY

Uf-value frame ?	1,6 W/(m ² · K)
Wind load resistance	class C3

FUNCTIONS

DIN direction	DIN left / right
Break-in resistance	up to RC 3
Opening type	side-hung, outward, inward
Max. sound insulation RwP	43 dB(A)

