

DOORS

RIVA ADS 65.NI

A versatile aluminum door system from BENEDICT + RIVA with building automation integration. The non-insulated RIVA AS 65.NI (Non Insulated) door system is outstandingly suited for use in indoor applications. The aluminum system is equipped with various security and convenience components, such as optional integration in the building automation and building security. Thus it can be individually adapted to upscale residential and commercial building plans.

From revolving doors and swinging doors to ultra-modern all-glass doors: The RIVA ADS 65.NI door system offers a multi-faceted implementation and design spectrum for exterior and interior areas. Additional creative freedom is ensured by design components, such as standard and corner glass strips, as well as center glazing. Thanks to RIVA system compatibility, standard solutions in the area of security are quite simple: With identical face widths the RIVA ADS 65.NI door system can be combined visually seamlessly with smoke doors and fire doors.



Product information:

- Fast and clampable fastening via the multi-function groove.
- With preassembled rotary slot stone
- Simple integration in the building automation and building security

DESIGN SPECIFICATIONS

Face width	137 mm
Window fittings concealed	yes
Element width max.	3180 mm
Element height max.	3220 mm

TECHNICAL SPECIFICATIONS

National technical approval	upon request
CE mark	yes
Verification of permanent functionality	200000 cycles in accordance with DIN EN 12400

SUSTAINABILITY

FUNCTIONS

DIN direction	DIN left / right
Break-in resistance	up to RC 2
Max. sound insulation RwP	44 dB(A)



We are experts in designing, manufacturing and installing complex facades.

