

WINDOWS

RIVA AWS 60

Excellent thermal insulation and versatile implementation possibilities. The outward opening windows from BENEDICT + RIVA are impressive with excellent thermal insulation, versatile implementation possibilities, and easy processing. The comfort level in the building is significantly increased with outward opening windows from RIVA, not least through the space that is gained. With a maximum size for top-hung windows of 2000 mm x 2000 mm and optional concealed fittings, there is a high degree of design freedom for the rigorous requirements of apartment and home construction.


Product information:

- Suitable for use in private apartment and home construction, as well as in commercial real estate
- Center gasket in co-extrusion
- Different opening types, optionally with concealed fittings

DESIGN SPECIFICATIONS

Face width min. 91 mm

Face width window frame min. - 51 mm
max.

Face width casement frame min. max. 40 mm

Face width mullion min. - max. 76 - 250 mm

SUSTAINABILITY

Corrosion protection class class 5

Uf-value frame ? 1,7 W/(m² ·K)

Wind load resistance class C5/B5

Certificates cradle2cradle SILVER

TECHNICAL SPECIFICATIONS	
Fall prevention	yes
Barrier-free operating force as specified in DIN 1840	yes
Operating forces	class 1
CE mark	yes

FUNCTIONS	
Barrier-free	? 20 mm
Break-in resistance	up to RC 2
Opening type to the outside	side-hung, double-vent side-hung / side-hung, projected top-hung, projected side-hung, horizontal pivot, vertical pivot
Opening type to the inside	turn / tilt, side-hung, bottom-hung, double-vent turn / tilt / side-hung, Double-vent side-hung / side-hung, tilt / slide, toplight, horizontal pivot, vertical pivot, tilt-before-turn



We are experts in designing, manufacturing and installing complex facades.

