

DOORS

RIVA ADS 70.HI

Robust exterior doors that guarantee high lock and key security – DIN tested. The RIVA exterior doors RIVA ADS 70.HI are doors that are unlike conventional house doors due to their robust design and fittings systems that are tested in accordance with DIN 18251. This exterior door is suitable for high-traffic areas and wherever lock and key security should be ensured. It can be integrated in the planned building automation and meets the highest energy-efficiency requirements. It offers a maximum sound reduction standard and in addition a barrier-free combination EPDM and aluminum threshold. For an architectural design that does not neglect a pleasant room climate.



Product information:

- For buildings with the most rigorous energy management requirements
- Ideal as a multi-function door for building automation
- Harmonizes effectively with facades and window systems

DESIGN SPECIFICATIONS

Face width	min. 147 mm
Vent variant	all-around, sill-rail profile
Filling type	insert panel infill, door infill, leaf enclosing on one side, door infill, leaf-enclosing on two sides
Overall system depth min. - max.	70 mm

TECHNICAL SPECIFICATIONS

National technical approval	upon request
CE mark	yes
Verification of permanent functionality	class 5
Vent weight max.	150 kg

SUSTAINABILITY

Differential climate behavior	class 2(d),2(e)
Uf-value frame ?	1,7 W/(m ² ·K)
Wind load resistance	class C3

FUNCTIONS

DIN direction	DIN left / right
Break-in resistance	up to RC 3
Opening type	side-hung, outward, inward
Max. sound insulation RwP	43 dB(A)

