

DOORS

RIVA ADS 50.NI

A versatile aluminum door system from BENEDICT + RIVA with building automation integration. The non-insulated RIVA AS 50.NI (Non Insulated) door system is outstandingly suited for use in indoor applications. The aluminum system is equipped with various security and convenience components, such as optional integration in the building automation and building security. Thus it can be individually adapted to upscale residential and commercial building plans.

From revolving, swinging and pull-push doors to ultra-modern all-glass doors: The RIVA ADS 50.NI door system offers a multi-faceted implementation and design spectrum for exterior and interior areas. The design components, such as standard and corner glass strips, as well as centered glazing elements, ensure additional design freedom



Product information:

- Fast and clampable fastening through the multi-function groove; with preassembled rotary slot stone
- Simple integration in the building automation and building security
- Available as revolving door, swing door, push-pull door, and all-glass door in many variants

DESIGN SPECIFICATIONS

Face width	min. 141 mm
Element width max.	1100 mm
Element height max.	2500 mm
Vent variant	all-around, sill-rail profile, adjustable sill

TECHNICAL SPECIFICATIONS

CE mark	yes
Verification of permanent functionality	class 5
Vent weight max.	200 kg
Glass/panel thickness min. - max.	6 - 32 mm

SUSTAINABILITY

Wind load resistance	class C3
----------------------	----------

FUNCTIONS

Anti-panic function	yes
Barrier-free	? 20 mm
DIN direction	DIN left / right
DIN direction	yes

